



SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name J-LOK RESIN CAPSULES
Synonym(s) J- LOK SINGLE SPEED RESIN • J-LOK 5 STAR RESIN • J-LOK DUAL SPEED RESIN • J-LOK G SERIES RESIN • J-LOK H SERIES RESIN CAPSULE • J-LOK POSTGROUT CABLE RESIN • J-LOK RESIN CAPSULE • J-LOK TENDON RESIN • SPIN2STALL® RESIN

1.2 Uses and uses advised against

Use(s) AS PER MANUFACTURER INSTRUCTIONS • BONDING AGENT • REINFORCEMENT
Resin anchoring grout contained within a plastic sheath used for support with rock bolts in mines & tunnels.

1.3 Details of the supplier of the product

Supplier name ROCBOLT RESINS PTY LTD
Address 40-44 Anzac Avenue, Smeaton Grange, NSW, 2567, AUSTRALIA
Telephone 02 4647 8388
Fax 02 4648 3444
Email asykes@rocboltresins.com.au
or
llaidler@rocboltresins.com.au
or
djoyce@rocboltresins.com.au

1.4 Emergency telephone number(s)

Emergency 04 3877 7714
Emergency 04 6721 6449

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

2.2 Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

2.3 Other hazards

Due to the product form (enclosed), contact with contents is not anticipated with normal use.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

| Ingredient | CAS Number | EC Number | Content |
|------------------|------------|-----------|---------|
| STYRENE | 100-42-5 | 202-851-5 | <12.5% |
| BENZOYL PEROXIDE | 94-36-0 | 202-327-6 | <1% |
| FILLER(S) | - | - | >50% |
| POLYESTER RESIN | - | - | <30% |

4. FIRST AID MEASURES

PRODUCT NAME J-LOK RESIN CAPSULES

4.1 Description of first aid measures

| | |
|-----------------------------|--|
| Eye | If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes. |
| Inhalation | If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing. |
| Skin | If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor. |
| Ingestion | For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form. |
| First aid facilities | None allocated. |

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases (carbon oxides, styrene, hydrocarbons) when heated to decomposition. Styrene may polymerise readily at elevated temperatures and may violently rupture sealed containers.

5.3 Advice for firefighters

Non flammable. Evacuate area and contact emergency services. Toxic gases (hydrocarbons, carbon oxides, styrene) may be evolved when heated. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool nearby storage areas.

5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate ventilation and fire protection systems.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

| Ingredient | Reference | TWA | | STEL | |
|------------------|-----------|-----|-------------------|------|-------------------|
| | | ppm | mg/m ³ | ppm | mg/m ³ |
| Benzoyl peroxide | SWA (AUS) | -- | 5 | -- | -- |
| Styrene, monomer | SWA (AUS) | 50 | 213 | 100 | 426 |

Biological limits

| Ingredient | Determinant | Sampling Time | BEI |
|------------|--|---------------|---------------------|
| STYRENE | Mandelic acid plus phenylglyoxylic acid in urine | End of shift | 400 mg/g creatinine |
| | Styrene in venous blood | End of shift | 0.2 mg/L |

Reference: ACGIH Biological Exposure Indices

8.2 Exposure controls

Engineering controls No information provided.

PPE

- Eye / Face** Wear splash-proof goggles.
- Hands** Wear barrier gloves.
- Body** Wear coveralls. With prolonged use, wear coveralls.
- Respiratory** Where an inhalation risk exists, wear a Type A (Organic vapour) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

| | |
|----------------------------------|---|
| Appearance | WHITE CATALYST PREMIX SEPARATED FROM RESIN MASTIC WITH PIGMENTS AND INERT FILLERS, ENCLOSED IN A CAPSULE FILM |
| Odour | SLIGHT STYRENE SMELL |
| Flammability | NOT APPLICABLE |
| Flash point | NOT APPLICABLE |
| Boiling point | NOT APPLICABLE |
| Melting point | NOT APPLICABLE |
| Evaporation rate | NOT APPLICABLE |
| pH | NOT APPLICABLE |
| Vapour density | NOT AVAILABLE |
| Specific gravity | 2.0 |
| Solubility (water) | INSOLUBLE |
| Vapour pressure | NOT APPLICABLE |
| Upper explosion limit | NOT APPLICABLE |
| Lower explosion limit | NOT APPLICABLE |
| Partition coefficient | NOT AVAILABLE |
| Autoignition temperature | NOT AVAILABLE |
| Decomposition temperature | NOT AVAILABLE |
| Viscosity | NOT AVAILABLE |
| Explosive properties | NOT AVAILABLE |
| Oxidising properties | NOT AVAILABLE |
| Odour threshold | NOT AVAILABLE |

9.2 Other information

| | |
|--------------------|----------------|
| % Volatiles | NOT APPLICABLE |
|--------------------|----------------|

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Styrene may polymerise with violent rupture/explosion. Polymerizes with evolution of heat. Avoid contact with curing agents, accelerators, and/or initiators.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), amines, halogens, sunlight, ferrous salts, heat and ignition sources. May polymerise with violent rupture/explosion.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon and styrene oxides, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Due to the product form (enclosed), contact with contents is not anticipated with normal use.

Information available for the ingredient(s):

| Ingredient | Oral Toxicity (LD50) | Dermal Toxicity (LD50) | Inhalation Toxicity (LC50) |
|------------------|----------------------|------------------------|----------------------------|
| STYRENE | > 2000 mg/kg (rat) | -- | 11.8 mg/L/4 hours (rat) |
| BENZOYL PEROXIDE | 5700 mg/kg (mouse) | > 1000 mg/kg | -- |

Skin Due to product encapsulation, the potential for skin contact with contents is reduced. If the container is damaged, contact may result in irritation, redness, pain, rash, dermatitis and possible burns. Effects may be delayed.

Eye Due to product encapsulation, the potential for eye contact with contents is reduced. If the container is damaged, direct contact may result in irritation, lacrimation and burns.

Sensitisation May cause an allergic skin reaction. This product is not classified as a respiratory sensitiser.

Mutagenicity Insufficient data available to classify as a mutagen.

Carcinogenicity Due to the product encapsulation, exposure to contents is not anticipated with normal use. Styrene is classified as possibly carcinogenic to humans (IARC Group 2B).

Reproductive Insufficient data available to classify as a reproductive toxin.

STOT - single exposure Over exposure may result in irritation of the nose and throat, coughing, nausea, vomiting, dizziness and breathing difficulties. High level exposure may result in respiratory paralysis and unconsciousness.

STOT - repeated exposure Due to product encapsulation, the potential for exposure to the contents is reduced. May cause damage to organs (nasal epithelial and ear) through prolonged or repeated exposure to styrene if inhaled.

Aspiration Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

PRODUCT NAME J-LOK RESIN CAPSULES

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

If released to the atmosphere, styrene will react rapidly with both hydroxyl radicals and ozone with a combined calculated half-life of about 5 hours. If released to environmental bodies of water, styrene will volatilise relatively rapidly and biodegrade, but is not expected to hydrolyse. If released to soil it will biodegrade and have low soil mobility.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal For small quantities, mix with other component/s, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information (if required). Ensure protective equipment is worn when mixing. Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

| | LAND TRANSPORT (ADG) | SEA TRANSPORT (IMDG / IMO) | AIR TRANSPORT (IATA / ICAO) |
|------------------------------------|----------------------|----------------------------|-----------------------------|
| 14.1 UN Number | None allocated. | None allocated. | None allocated. |
| 14.2 Proper Shipping Name | None allocated. | None allocated. | None allocated. |
| 14.3 Transport hazard class | None allocated. | None allocated. | None allocated. |
| 14.4 Packing Group | None allocated. | None allocated. | None allocated. |

14.5 Environmental hazards

No information provided.

14.6 Special precautions for user

Hazchem code None allocated.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

Hazard codes None allocated.

Risk phrases None allocated.

Safety phrases None allocated.

Inventory listing(s) **AUSTRALIA: AICS (Australian Inventory of Chemical Substances)**
All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information ORGANIC PEROXIDES: Fires involving organic peroxides can be intense and move rapidly due to product rapid decomposition with release of oxygen and may involve explosions. If spilt on combustible materials it may spontaneously ignite. A diluent is often added to organic peroxides to reduce shock sensitivity.

PRODUCT NAME J-LOK RESIN CAPSULES

IARC GROUP 2B - POSSIBLE HUMAN CARCINOGEN. This product contains an ingredient which has demonstrated sufficient evidence to have been classified by the International Agency for Research into Cancer (IARC) as possibly carcinogenic to humans and whose use should be strictly monitored and controlled.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

| | |
|-------------------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists |
| CAS # | Chemical Abstract Service number - used to uniquely identify chemical compounds |
| CNS | Central Nervous System |
| EC No. | EC No - European Community Number |
| EMS | Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods) |
| GHS | Globally Harmonized System |
| GTEPG | Group Text Emergency Procedure Guide |
| IARC | International Agency for Research on Cancer |
| LC50 | Lethal Concentration, 50% / Median Lethal Concentration |
| LD50 | Lethal Dose, 50% / Median Lethal Dose |
| mg/m ³ | Milligrams per Cubic Metre |
| OEL | Occupational Exposure Limit |
| pH | relates to hydrogen ion concentration using a scale of 0 (highly acidic) to 14 (highly alkaline). |
| ppm | Parts Per Million |
| STEL | Short-Term Exposure Limit |
| STOT-RE | Specific target organ toxicity (repeated exposure) |
| STOT-SE | Specific target organ toxicity (single exposure) |
| SUSMP | Standard for the Uniform Scheduling of Medicines and Poisons |
| SWA | Safe Work Australia |
| TLV | Threshold Limit Value |
| TWA | Time Weighted Average |

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

[End of SDS]