

## CUTTABLE SUPPORT

**FIBREGLASS 32MM RIB BOLT****Features**

- High capacity fibreglass dowels
- Used where high corrosion rates or grout/resin injection is carried out
- Suitable for use with common mine site cable bolting consumables:
  - o 42 – 45mm drill bit
  - o 36mm diameter resin capsules
  - o Cable bolt grouts
- 46mm Hex Nut
- Purpose designed installation spanners and grout connectors available
- For use with purpose designed 300mm x 300mm square high capacity steel plastic combination plate
- Custom configurations are available including;
  - o Resin anchored, tensioned, post grouted dowel
  - o Simple fully grouted dowel
  - o Fully resin encapsulated thrust dowel
- Hollow dowels stocked in 3m and 4m lengths
- Solid dowels stocked in 1.5m and 2.1m lengths



Type	Outside Diameter (mm)	Inside Diameter (mm)	UTS Rod (tonne)	UTS with Nut (Tonne)	Rod Single Shear Strength (kN)	Shank Torque (N.m)	Pressure Rating (Bar)
Hollow	32	15	35	9	90	>200	100
Solid	32	n/a	45	12	130	>300	n/a

**Packaging:** Customer specific packaging is available

**Colour Code:** ALL 32mm Dowels and Nuts are white

Jenmar Australia Pty Ltd products are manufactured and supplied to the specifications shown on our product information sheets, or to an agreed customer specification. The customer (purchaser) is responsible for checking the suitability of products for their intended use. Furthermore, we make no representation about the time or costs associated with your installation of the products.