

## RESIN CAPSULES &amp; ACCESSORIES

**SPIN2STALL®****Features**

- Increased productivity – no waiting for resin to cure before tightening the nut
- No counting of spin or hold times – consistent installations
- Self-auditing bolt installation - based upon remnant thread length of the bolt which provides an indication of the standard of installation
- High pre-tension levels can still be achieved
- Extensive research and independent testing shows minimal damage to resin bond using spin to stall technique
- Uses a J-Lok dual speed accelerated specifically formulated cure resin capsule and Jenmar bolt with engineered accurate and reliable pin break out level
- Available in fast set speeds usually incorporating 50:50 proportions of Fast A speed: Slow set



Capsule Length (mm)	1000	1100 -1500
Quantity/Box	25	20
Quantity/Pallet	1050	840

Shear Strength (MPa)	>22
Shelf Life	4 months

\*Relevant specifications are taken at 25°C

SPIN2STALL® is a registered trade mark of FCI Holdings Delaware, Inc



To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule (**eg 1200mm capsule = 12 sec**).

Continue mixing at the back of the hole until the bolt is tightened to motor stall

[www.jenmar.com.au](http://www.jenmar.com.au) • +61 2 4648 7500