

CABLE BOLTS

HYDRAULIC TENSIONING EQUIPMENT

	Part Number	Description	Application
Tensioner Units	TENS27T	27 tonne tensioner, 22mm cable 10 000 psi Max Working Pressure Head Only	Used for ALL SuperStrand configurations
	TENS2728	27 tonne tensioner, 28mm cable 10 000 psi Max Working Pressure	Used for all TG Bolt + SUMO configurations
	TENS2715	10 tonne tensioner, 15.2mm cable 10 000 psi Max Working Pressure	15.2mm trussing
	TENSHOSES	Twin 6m long hydraulic hoses, 10000 psi working pressure Compliant with MDG41 guidelines	Cable tensioning hoses
	TENSAIR	Air/hydraulic intensifier. 10 000 psi Max Working Pressure Complete with: - 6m x 10 000 psi hydraulic hoses - Pressure gauge - Air line filter - Air line lubricator	Used with all cable tensioners - can be internally regulated for tensioners operating at lower than 10 000 psi.
Tensioning Consumable	JTW22	22mm Tensioner Wedge	Internal tensioner wedge for TENS27T and TENS12T tensioner and SuperStrand cables
	JTW28	28mm Tensioner Wedge	Internal tensioner wedges for use with the TENS2728 tensioner and TG Bolt or SUMO
	JTWA22	22mm Tensioner Wedge complete with screws	Internal tensioner wedge for CRAM built lightweight tensioners and SuperStrand cables
	JTWA28	28mm Tensioner Wedge complete with screws	Internal tensioner wedge for CRAM built lightweight tensioners for TG Bolt and SUMO
	JTW15	15.2mm Tensioner Wedge	Internal tensioner wedge for TENS2715 tensioner and 15.2mm cables

27t x 22mm tensioners are colour coded yellow ■

10t x 15.2mm tensioners are colour coded blue ■

27t x 28 mm tensioners are colour coded green ■

