

CUTTABLE SUPPORT

FIBREGLASS 32MM BOLT**Features**

- High capacity secondary support fibreglass dowels
- Used where coal extraction includes cutting of rib support dowels
- Suitable for use with common mine site cable bolting consumables:
 - o 42 – 45mm drill bit
 - o 36mm diameter resin capsules
 - o Cable bolt grouts
- 46mm Hex Nut
- Purpose designed installation spanners and grout connectors available
- For use with purpose designed 300mm x 300mm square high capacity steel plastic combination plate
- Custom configurations are available including;
 - o Resin anchored, tensioned, post grouted dowel
 - o Simple fully grouted dowel
 - o Fully resin encapsulated dowel
- Hollow dowels stocked in 3m and 4m lengths
- Solid dowels stocked in 1.5m and 2.1m lengths
- Do not store these products in direct sunlight



Type	Outside Diameter (mm)	Inside Diameter (mm)	UTS Rod (tonne)	UTS with Nut (tonne)	Rod Single Shear Strength (kN)	Shank Torque (N.m)	Pressure Rating (Bar)
Hollow	32	15	35	9	90	>200	100
Solid	32	n/a	45	12	130	>300	n/a

Packaging: Customer specific packaging is available

Colour Code: ALL 32mm Dowels and Nuts are white