

## ROCK BOLTS

**END FITTINGS**

	Part Number	Description	Application
Nuts	NUTRM24H125DM	Plain M24 class 8 nut, 30mm high	Spare molycoated nuts for hanging brackets or floor bolting
	NUT34H1D	Plain 3/4" UNC class 8 nut, 25mm high	Spare nuts for hanging brackets
	NUTRM24H125DGAL	Galvanised M24 class 8 nut, 30mm high	Spare nuts galvanised bolts
Washers	WASHM24DB	Dome Ball, 51mm O.D., 24mm I.D.	Used on roof bolts with volcano plates
	WASHM24DBG	Galvanised dome Ball, 51mm O.D., 24mm I.D.	Used on galvanised roof bolts with volcano plates
	WASH25MML	Flat hardened steel washer, 65mm O.D., 25mm I.D.	Used on 3/4" bolts
	WASH25MM	Flat steel washer, 48mm O.D., 25mm I.D.	Used on M24 bolts
	WASHWT	White teflon anti friction washer M24	Used on M24 Bolts
Expansion Shells	EXPD10L	D10L 2-leaf expansion shell, 3/4" UNC thread	Conventional Bolts – 35mm drill hole
	ES2443RHT	M24 Right hand thread 3 leaf expansion shell	For 24mm eye bolts, L Pins and hanger bolts
	EB20CS	M20 Right hand thread 3 leaf expansion shell	For 20mm eye bolts, L Pins
	EB16CS	M16 Right hand thread 2 leaf expansion shell	For 16mm eye bolts, L Pins
Resin Shredder	S	Resin Shredder	Prevent gloving and ensure resin mixing
Shotcrete Depth	IW – White = 3.0m Bolt IY – Yellow = 2.4m Bolt	Shotcrete Depth Indicator	Provide QA/QC for easy application and control of fibrecrete depth

Note: 1 ft.lb = 1.36 N.m

**Features**

- Plain Nuts, Dome Balls and Plas Nuts are available as Galvanised Product code "G" added to end of part number
- Nuts and washers are packaged 50 per 4 litre bucket