

MIXING SPANNERS

HARD ROCK PARTS LIST

	Socket Code	Description	Application
Cable Bolt Spanners	28	TGBolt Drive c/w water flushing seal – painted GREEN	TGBolt
	20	SuperStrand drive located internally at base of spanner to fit over 21.8mm x 19 wire cable – Painted RED	SuperStrand
	21	Combined drive in base of spanner with a standard 36mm Hex A.F. socket on top. Painted RED	SuperStrand & roof bolts
	14	Replaceable drive, round socket with grub screw on top of spanner to suit replaceable “flower” drives. Painted RED	Any sized cable bolt
Rock Bolt Spanners	5	Standard 36mm Hex A.F. socket , with high tensile seat to prevent wear.	Torque Tension, Hex Forged Head Bolts
	T3875036AF	Hard Rock Dollie, available ex stock in 750 and 900mm lengths	For hand held 20mm JTech Bolt
	JDOPANTHER36AF	Hand held 36AF Dollie for resin bolts 600mm long	For hand held 20mm JTech Bolt
	T38D46FL JDO33FLS T38D39FL	Friction Lok dollie for 47and 39mm and 33mm hand held Friction Loks	Jumbo and panther friction lok installation
Dollies	T38MLOK24036AF	Mech Lok Dolly	T38F to 36AF Drive 200mm
	T38MSR600T38F	Speed Rod	T38F to T38m 600mm
	T38WIL90036AF	Wilco Dolly	Jumbo Dolly for J-Tech Bolt
	T38MSR600T45F	Speed Rod	T45F to T38m 600mm

Drive Code	Description
-	T38 to suit Tamrock Jumbo rig
-	R38 to suit Atlas Copco Rig

