



PRODUCT CATALOGUE

COAL MINING

MISSION STATEMENT

JENNMAR Australia Pty. Ltd. is a leader and innovator in the design and manufacture of roof and ground control systems for the mining, tunneling and construction industries.

We are dedicated to providing our customers with competitively priced quality products and services as well as increasing the productivity of our customers, whilst maintaining an environment:

- Which generates growth for our stockholders
- Where the commitment, skills and creativity of our employees can flourish and be rewarded
- Which ensures the safety and welfare of our employees
- Where we enhance our community



Contacts

Peter Craig

National Manager – Coal
E-mail: pcraig@jennmar.com.au
Mobile: 0419 018 998

New South Wales

Tim Gaudry

NSW Mine Service Manager
E-mail: tgaudry@jennmar.com.au
Mobile: 0409 120 426

Brett Goodman

Northern Mine Service Representative
E-mail: bgoodman@jennmar.com.au
Mobile: 0427 705 693

Mark Corrigan

Southern Mine Service Representative
E-mail: mcorrigan@jennmar.com.au
Mobile: 0418 828 344

Paul Gibbons

Western NSW Mine Service Representative
E-mail: pgibbons@jennmar.com.au
Mobile: 0428 423 504

Scott Wensemious

North West Mine Service Representative
E-mail: swensemious@jennmar.com.au
Mobile: 0417 669 308

Queensland

Joel Danger

Mine Service Representative
E-mail: jdanger@jennmar.com.au
Mobile: 0419 194 480

Matthew Benjamin

Mine Service Representative – Emerald
E-mail: mbenjamin@jennmar.com.au
Mobile: 0488 777 756

Danny Murrill

Product Training Manager
E-mail: dmurrill@jennmar.com.au
Mobile: 0408 859 007

Contacts

Manufacturing and Administration

Head Office and Plant

40-44 Anzac Avenue
Smeaton Grange NSW 2567
Phone: 02 4648 7537
Fax: 02 4648 7555

Peter Roberts

Managing Director
E-mail: proberts@jennmar.com.au
Mobile: 0418 687 371

Matthew Berry

Commercial Manager
E-mail: mberry@jennmar.com.au
Mobile: 0408 269 658

Armand du Plessis

National Quality Manager
E-mail: aduplessis@jennmar.com.au
Mobile: 0417 905 046

Paul Gregg

Chief Operating Officer
E-mail: pgregg@jennmar.com.au
Mobile: 0447 771 475

Michael Sveronis

Plant Manager NSW
E-mail: msveronis@jennmar.com.au
Mobile: 0408 209 156

Blair Moses

National Safety & Environmental Manager
E-mail: bmoses@jennmar.com.au
Mobile: 0455 612 821

Queensland Plant

48-52 Southgate Drive Paget QLD 4740
Phone: 07 4952 8700
Fax: 07 4952 8777

Kurri Kurri (NSW)

43 Wermol Street Kurri Kurri NSW 2327
Phone: 02 4936 5200

Western Australian Plant

84 Furniss Rd Landsdale WA 6065
Phone: 08 94089900

Mick Baker

Queensland Manager
E-mail: mbaker@jennmar.com.au
Mobile: 0427 543 664

Keith Coburn

Plant Manager Queensland
E-mail: kcoburn@jennmar.com.au
Mobile: 0408 605 546



Contents

Mission Statement	2
Contacts	3-4
ROCK BOLTS & ROCK BOLT ACCESSORIES	
M24 JX Torque Tension Bolt.....	7
M24 JBX Torque Tension Bolt.....	8
M24 JBS Torque Tension Bolt.....	9
3/4" JSD Paddle Bolt	10
33mm Friction Lok Bolt.....	11
M36 Boot Bolt	12
M24 Tension Indicator Washer.....	13
Cover Drive	14
Floor Bolt Extension	15
Torque Test Nut.....	16
36 A.F. Dolly	16
"U" Hanger Nuts	17
M24 Nut	17
M24 Dome Ball Washer	17
CABLE BOLTS & CABLE BOLT ACCESSORIES	
100T Goliath Cable Bolt.....	19
100T Bulbed Goliath Cable Bolt.....	20
31mm 70T SUMO TEX Cable	21
70T 12 Wire Sumo Cable Bolt.....	22
31mm JW10 TEX Cable	23
70T 10 Wire Hollow Cable Bolt.....	24
Superstrand Cable Bolt.....	25
15.2mm Twin Strand Tendons & Trusses.....	26
15.2mm Triple Strand Tendons & Trusses.....	27
18mm Twin Strand Tendons & Trusses.....	28
18mm Triple Strand Tendons & Trusses	29
31mm Barrel & Wedge.....	30
28.6mm Barrel & Wedge.....	31
21.8mm Barrel & Wedge.....	31
18mm Barrel & Wedge.....	32
15.2mm Barrel & Wedge.....	32
Trussing Splice Tube	33
Grout Guns	33
Grout Lance – Screw In.....	34
Push-Clamp on Grout Guns	34
Grout and Breather Tube	35
30T Tensioners.....	36
Tiger Dollie	37
Dolly suit TEX cables.....	37
Dolly To 21.8mm Superstrand.....	38

PLATES

Kanga Plate	40
Roof Bolt Volcano Plate.....	41
Groutable Cable Volcano Plate TEX, 70T Sumo & Hollow Cables	42
Cable Volcano Plate - Goliath.....	43
Cable Volcano Plate - Superstrand	44
Flat Plate	45
Domed Butterfly Plate	46
Surface Support Plates.....	47

MESH TILE

Steel Roof Mesh Module.....	49
Steel Rib Mesh Sheet.....	50
Plastic Mesh	51
Fibreglass Mesh.....	52

SPECIALTY GROUT & CEMENT

Bottom-Up 100 MPa Grout	54
Top-Down 80 MPa Grout.....	55
Top-Down 80 Plus Grout.....	56
J-PLUG Grout.....	57
J-URR GROUT (Jennchem Underground Roadway Repair)	58


RESIN CAPSULES

SPIN2STALL® Resin Capsules	60
Standard Dual Speed (Oil Based Catalyst) Resin Capsules.....	61
Standard Single Speed (Oil Based Catalyst) Resin Capsules.....	62
'5 Star' Dual Speed (Water Based Catalyst) Resin Capsules..	63
'5 Star' Single Speed (Water Based Catalyst) Resin Capsules....	64
Post Grout Cable (Water Based Catalyst) Resin Capsules.....	65
Post Grout Cable (Oil Based Catalyst) Resin Capsules	66
Twin 'H' Resins (Oil Based Catalyst) Resin Capsules	67

CUTTABLE SUPPORT & CUTTABLE SUPPORT ACCESSORIES

32mm Torque Tension Bolt	69
32mm Geodowel.....	70
22mm Thrust Dowel.....	71
25mm Thrust Dowel.....	72
22mm Extra High Torsion (XHT) Tensionable Bolt	73
Plastic Plates: 22 - 25mm Dowels	74
Plastic Steel Combination Plates - 22-25mm Dowels	75
Plastic Steel Combination Plates - 32mm Dowels	76
46 A.F. Dolly.....	77
Grout Connector Suit 32mm Dowels.....	77

ROCK BOLTS & ROCK BOLT ACCESSORIES



Rock Bolts


M24 JX Torque Tension Bolt








Features:

- The preferred primary roof support bolt by Australian coal mines
- The "X" grade steel used by JENNMAR has a superior toughness and ductility through the use of grain refining alloys. The JENNMAR "X" grade bolts provide better performance in mines where Stress Corrosion Cracking is evident and also in areas of high localized horizontal stresses
- All nuts are coated with a dry film molycoat to provide low friction and corrosion resistance
- All nuts are connected to the bolt by a shear-pin with varying ranges of torque breakout strength

Property	Minimum Value	Typical Value
Yield strength (kN)	218	246
Ultimate Tensile strength (kN)	305	348
Shear Strength (kN)	213	243
Elongation %	15	19
Bar core diameter (mm)	21.5	21.7
Cross sectional area (mm ²)	363	378
Rib height (mm)	1.1	1.5
Rib Spacing (mm)	23	30
Mass/meter (kg/m)	2.8	3

Steel grade colour code	
-------------------------	--

Bolt length (m)	Colour code
1.2	
1.5	
1.8	
2.1	
2.4	

High ribbed bar for improved resin mixing and higher load transfer

To suit drill bit 27 – 28mm

Available plain or hot dipped galvanized

Rock Bolts


M24 JBX Torque Tension Bolt








Features:

- The "X" grade steel used by JENNMAR has a superior toughness and ductility through the use of grain refining alloys. The JENNMAR "X" grade bolts provide better performance in mines where Stress Corrosion Cracking is evident and also in areas of high localized horizontal stresses
- All nuts are coated with a dry film molycoat to provide low friction and corrosion resistance
- All nuts are connected to the bolt by a shear-pin with varying ranges of torque breakout strength

Property	Minimum Value	Typical Value
Yield strength (kN)	218	246
Ultimate Tensile strength (kN)	305	348
Shear Strength (kN)	213	243
Elongation %	15	19
Bar core diameter (mm)	21.5	21.7
Cross sectional area (mm ²)	363	378
Rib height (mm)	0.5	1
Rib Spacing (mm)	9	13
Mass/meter (kg/m)	2.8	3

Steel grade colour code	
-------------------------	--

Bolt length (m)	Colour code
1.2	
1.5	
1.8	
2.1	
2.4	

To suit drill bit 27 – 28mm

Rock Bolts

M24 JBS Torque Tension Bolt



Features:

- Mild steel bolts are commonly used for development rib support and longwall bolt-up roof support
- All nuts are coated with a dry film molycoat to provide low friction and corrosion resistance
- All nuts are connected to the bolt by a shear-pin with varying ranges of torque breakout strength

Property	Minimum Value	Typical Value
Yield strength (kN)	109	129
Ultimate Tensile strength (kN)	160	185
Shear Strength (kN)	112	130
Elongation %	22	27
Bar core diameter (mm)	21.5	21.7
Cross sectional area (mm ²)	363	378
Rib height (mm)	0.5	1
Rib Spacing (mm)	9	13
Mass/meter (kg/m)	2.8	3

Steel grade colour code	
-------------------------	--

Bolt length (m)	Colour code
1.2	
1.5	
1.8	
2.1	
2.4	

To suit drill bit 27 – 28mm

Available plain or hot dipped galvanised

Rock Bolts

3/4" JSD Paddle Bolt



Features:

- 22mm wide paddles on the insertion end promotes shredding of the resin capsule film and efficient mixing in 27 – 28mm diameter holes
- Normally used for rib support as a lightweight alternative to M24 Bolts when high strength is not required
- Can be readily installed with hand operated “windy borers”
- Available with a 3mm ‘C’ break out pin

Property	Minimum Value	Typical Value
Yield strength (kN)	66	78
Ultimate Tensile strength (kN)	98	116
Shear Strength (kN)	68	76
Elongation %	22	27
Bar core diameter (mm)	17	17.4
Cross sectional area (mm ²)	227	238
Rib height (mm)	1	1.4
Rib Spacing (mm)	7	11
Mass/meter (kg/m)	1.85	1.95

Steel grade colour code	
-------------------------	--

Bolt length (m)	Colour code
1.2	
1.5	
1.8	
2.1	

To suit drill bit 27 – 28mm

Rock Bolts

33mm Friction Lok Bolt



Features:

- The radial compression of the slotted steel tube inside a borehole provides both radial and axial restraint to rock movement
- Used as rib support in some coal mines when crushed coal rib prevent resin capsule insertion
- Minimal bolt tail protrudes into the roadway
- Can be post grouted for extra corrosion protection and support capacity
- Available in black or hot dipped galvanized

Property	Minimum Value	Typical Value
Yield strength (kN)	80	100
Ultimate Tensile strength (kN)	100	120
Cross sectional area (mm ²)	-	204
Mass/meter (kg/m)	-	1.53

To suit drill bit 30 – 32mm

Rock Bolts

M36 Boot Bolt



Features:

- High strength & ductility, 33 mm diameter bolt for pinning conveyor equipment to the mine floor
- High ductility reduces likelihood of fatigue failures due to the constantly changing load conditions of the conveyor equipment
- Designed for installation with common coal mine equipment – 42mm cable bolt drill bits, 36mm diameter cable bolt resin capsules
- Separate drive nut allow spinning into the hole using regular roof bolt spanners. Drive nut part # NUTM36DRIVE
- Special 100 x 100mm plate designed to fit the common “boot end” base plates. Accommodates installation angles up to 15 degrees
- Standard length 1800mm

Property	Typical Value
Yield strength (kN)	284
Ultimate Tensile strength (kN)	412
Shear Strength (kN)	275
Elongation %	30
Bar core diameter (mm)	33
Cross sectional area (mm ²)	855
Paddle width (mm)	36-38
Paddle Spacing (mm)	50
Mass/meter (kg/m)	6.7

Bolt length (m)	Colour code
1.2	Blue
1.5	Yellow
1.8	Red
2.1	Green

To suit drill bit 42mm

Rock Bolt Accessories

M24 Tension Indicator Washer



Features:

- Centralising corner lugs to match the standard M24 Dome ball
- Collapses/inverts uniformly at the rated tension load and torque
- Used in conjunction with mated flat washer to prevent frictional heating or damage to the tension indicator washer
- Washer does not collapse onto the thread and can be removed by hand if the nut is taken off
- Coloured RED dome is hidden when the correct load is applied

Dimensions (mm)	52 x 52
Load at Collapse (tonnes)	6 - 8

Rock Bolt Accessories

Cover Drive



Features:

- Allows a resin anchored bolt to be installed in competent coal behind the crush-zone Improves rib bolting efficiency in broken rib conditions
- Designed to complement existing rib bolting processes and acts as a physical support to prevent borehole collapse
- Installed with a specialized drill steel and the coverdrive is left in the hole as the drill steel is retracted
- To suit bolt anchorage holes drilled with 27 – 28mm drill bits
- Patented

Length (mm)	Diameter (mm)	Mass (kg)
600	50	0.157

Rock Bolt Accessories

Floor Bolt Extension



Features:

- Commonly used for forming floor bolts for pinning boot ends etc, this section is removed and re-used
- Can be used as extensions to existing mild steel rock bolts for hanging
- Hex drive allows for easy removal from floor bolts
- Optional to come with or without nut and dome balls
- After removal, no bolt tails are left protruding from the floor eliminating trip hazards

Property	Typical Value
Threaded Stem Yield strength (kN)	118
Threaded Stem UTS (kN)	177
Threaded Stem Elongation %	27
Threaded stem length (mm)	300
Coupler diameter (mm)	35
Coupler steel grade	K1137
Coupler length (mm)	75
Drill hole diameter	43 - 45
Hex drive (mm)	18

Rock Bolt Accessories

Torque Test Nut



Features:

- A high torque roll pin with break-out set to 250-270 N.m break-out
- Colour coded bright pink nut to distinguish from regular bolts
- Can be placed within every bolting pod to ensure bolting rigs are regularly checked for torque output
- The bolt can be installed as part of the normal support pattern, with the high tensile nut being fully rated for X grade roof bolts
- A successful break-out indicates the bolting rigs are able to exceed 8 tonnes pre-tension on normal roof bolts

Bolt Thread	Torque Break-out (Nm)
M24	250-270

36 A.F. Dolly



Features:

- 36mm A.F. socket to suit standard rock bolt installations
- 25mm locking square drive suitable for common coal mining rock bolting rigs

Drive (mm)	Length (mm)	Socket (mm)
25 square	300-600	36 Hex

Rock Bolt Accessories

"U" Hanger Nuts



Features:

- 10mm diameter "U" hanger
- Available in all thread types
- Readily threaded onto the base of rock bolts for use as a hanger
- Recommended for carrying static loads
- Not recommended for lifting or pulling
- Avoid side loading of the "U" hanger

Length (mm)	Width (mm)	Mass (kg)	Load Rating (tonne)
92	56	0.28	2

M24 Nut



Features:

- M24 x 3 hot forged nut to suit M24 Rock Bolts
- Suitable for 'X' and 'S' grade rock bolts

Hex dimension (mm)	Length (mm)	Mass (kg)	Proof Load (kN)	Steel grade
36 A.F.	30	0.17	379.5	AS/NZS 4291.2:1995 class 8

M24 Dome Ball Washer



Features:

- Hot forged dome ball washer to suit M24 rock bolts

Outside Diameter (mm)	Length (mm)	Mass (kg)	Steel Grade
50	15	0.13	Medium carbon steel

CABLE BOLTS & CABLE BOLT ACCESSORIES



Cable Bolts

100T Goliath Cable Bolt



Features:

- 100 tonne capacity cable bolt
- Highest capacity cable on the market but still maintains flexibility for manual handling during installation
- Pre-tensioning jacks available up to 30 tonne
- 80 tonne capacity high tensile plates are available in relatively light weight 14mm thick steel

Typical Applications:

- Goliath of any length can be readily installed with hand bolters and hydraulic rigs as a point anchored, pre-tensioned support
- The 4m Goliath can be fully encapsulated with resin installed alongside primary support at the face. Installation time between 6 - 8 minutes

Property	Typical Value
Strand diameter (mm)	28.6
Number wires	19
Wire type	smooth
Steel area (mm ²)	532
Mass (kg/m)	4.2
Typical yield strength (kN)	850
Typical Ultimate tensile strength (kN)	970
Breaking load with barrel & wedge (kN)	785
Elongation %	5 - 7

Cable length (m)	Colour code
4.0	Green
6.0	Red
8.0	Yellow
10.0	

To suit drill bit 35mm

Resin capsules available to obtain encapsulation length up to 4m

Cable Bolts

100T Bulbed Goliath Cable Bolt



Features:

- 100 tonne capacity cable bolt
- Highest capacity cable on the market but still maintains flexibility for manual handling during installation
- Bulbed Goliath offers higher capacity anchorage over shorter encapsulation length
- Pre-tensioning jacks available up to 30 tonne
- 80 tonne capacity high tensile plates are available in relatively light weight 14mm thick steel

Typical Applications:

- Bulbed Goliath of any length can be readily installed with hand bolters and hydraulic rigs as a point anchored, pre-tensioned support

Property	Typical Value
Strand diameter (mm)	28.6
Number wires	19
Wire type	smooth
Bulb diameter (mm)	35
Bulb spacing (mm)	300
Steel area (mm ²)	532
Mass (kg/m)	4.2
Typical yield strength (kN)	850
Typical Ultimate tensile strength (kN)	970
Breaking load with barrel & wedge (kN)	785
Elongation %	5 - 7

Cable length (m)	Colour code
4.0	Green
6.0	Red
8.0	Yellow
10.0	

To suit drill bit 42mm

Resin capsules available to obtain encapsulation length up to 2.5m

Cable Bolts

31mm 70T SUMO TEX Cable



Features:

- 70 tonne capacity, 12 wire hollow cable bolt
- Fully bulbed, smooth wire for both high axial and shear performance when fully grouted
- Eliminates the need for hazardous hydraulic tensioners
- 8-10 tonne pre-tension is achievable off most hydraulic bolting rigs
- The threaded TEX end fitting achieves full tensile capacity of the wires
- Light weight high capacity 12mm plates available

Property	Typical Value
Strand diameter (mm)	31
Number wires	12
Wire type	smooth
Bulb diameter (mm)	36
Bulb spacing (mm)	500
Steel area (mm ²)	385
Mass (kg/m)	3.5
Typical yield strength (kN)	640
Typical Ultimate tensile strength (kN)	705
Breaking load with TEX end fitting (kN)	705
Elongation %	5 - 7

Cable length (m)	Colour code
4.0	Green
6.0	Red
8.0	Yellow
10.0	

To suit drill bit 42 - 45mm

Cable Bolts









70T 12 Wire Sumo Cable Bolt



Features:

- Higher 70 tonne capacity SUMO cable bolt
- 12 wires increases flexibility and capacity
- Large 14mm I.D. central flexible corrugated grout tube
- Increased flexibility makes handling in confined areas easier and reduces the risk of manual handling related injuries
- Standard 31mm diameter and hex drive to suit existing cable bolting accessories i.e. dollies, tensioners and grout lances
- Birdcaged along the entire length for maximum load transfer
- Smooth wires for optimum performance in shear
- Plated with new higher capacity 12mm thick volcano plates with grout indicator slots.
- Plates available for trussing
- Lengths available up to 14 m

Property	Typical Value
Strand diameter (mm)	31
Number wires	12
Wire type	smooth
Bulb diameter (mm)	36
Bulb spacing (mm)	500
Steel area (mm ²)	362
Mass (kg/m)	3.5
Typical yield strength (kN)	640
Typical Ultimate tensile strength (kN)	705
Breaking load with barrel & wedge (kN)	640
Elongation %	5 - 7

Cable length (m)	Colour code	
4.2		
6.2		
8.2		
10.2		

To suit drill bit 42 – 45 mm

Cable Bolts

31mm JW10 TEX Cable



Features:

- 70 tonne capacity, 10 wire hollow cable bolt
- Fully bulbed, smooth wire for both high axial and shear performance when fully grouted
- Eliminates the need for hazardous hydraulic tensioners
- 8-10 tonne pre-tension is achievable off most hydraulic bolting rigs
- The threaded TEX end fitting achieves full tensile capacity of the wires
- Light weight high capacity 12mm plates available

Property	Typical Value
Strand diameter (mm)	31
Number wires	10
Wire type	smooth
Bulb diameter (mm)	36
Bulb spacing (mm)	500
Steel area (mm ²)	385
Mass (kg/m)	3.5
Typical yield strength (kN)	640
Typical Ultimate tensile strength (kN)	705
Breaking load with TEX end fitting (kN)	705
Elongation %	5 - 7

Cable length (m)	Colour Code
4.2	Green
6.2	Red
8.2	Yellow
10.2	

To suit drill bit 42 – 45 mm

Cable Bolts

70T 10 Wire Hollow Cable Bolt



Features:

- 70 tonne capacity, 10 wires
- Smooth wires for improved strength against shearing
- Standard 31mm diameter and hex drive to suit existing cable bolt accessories i.e. dollies, tensioners and grout lances
- Birdcaged along entire length for maximum load transfer
- Point anchored with J-LOK "Post-Grout" resin capsules, specifically designed for mixing in larger drill holes
- Top-down grouted using thixotropic grout
- Plated with new higher capacity 12mm thick volcano plates with grout indicator slots.
Available in 200x200mm and 300x300mm sizes.
- Plates available for trussing
- Lengths available up to 10m

Property	Typical Value
Strand diameter (mm)	31
Number wires	10
Wire type	smooth
Bulb diameter (mm)	36
Bulb spacing (mm)	500
Steel area (mm ²)	362
Mass (kg/m)	3.5
Typical yield strength (kN)	640
Typical Ultimate tensile strength (kN)	705
Breaking load with barrel & wedge (kN)	640
Elongation %	5 - 7

Cable length (m)	Colour code
4.2	Green
6.2	Red
8.2	Yellow
10.2	

To suit drill bit 42 – 45 mm

Cable Bolts

Superstrand Cable Bolt



Features:

- Flexible and easy to handle even around the tight working areas of bolting rigs and continuous miner platforms
- Plain SuperStrand of any length can be readily installed with hand bolters as point anchored, pre-tensioned support
- The 4m SuperStrand can be “fully encapsulated” with resin installed alongside primary support at the face. Installation time between 6 – 8 minutes
- Special “through-the-chuck” drill motors allow full resin encapsulation of SuperStrands up to 8m in length

Property	Typical Value
Strand diameter (mm)	21.8
Number wires	19
Wire type	smooth
Steel area (mm ²)	313
Mass (kg/m)	2.5
Typical yield strength (kN)	525
Typical Ultimate tensile strength (kN)	590
Breaking load with barrel & wedge/ToTo (kN)	510
Elongation %	5 - 7

ToTo Diameter (mm)	ToTo Length (mm)	ToTo Torque:Tension Ratio (Nm: tonnes)
70	150	40:1

Cable length (m)	Colour code
4.0	Green
6.0	Red
8.0	Yellow
10.0	

To suit drill bit 27 – 28mm

Resin capsules available to obtain encapsulation length up to 4m

Cable Bolts








15.2mm Twin Strand Tendons & Trusses



Features:

- Low cost to capacity cable bolt configurations for the coal mining industry
- Can be used in either top-down or bottom-up grouting applications
- Typically fitted with fish-hooks to hold the cables inside the drill holes
- Truss configurations are available for ease of manually bending and tensioning cross members
- Birdcage spacing at 180mm for maximum bond strength with the grout and rock

Property	Typical Value
Strand diameter (mm)	15.2
Wire type	smooth
Bulb diameter (mm)	25
Bulb spacing (mm)	180
Steel area (mm ²)	280
Mass (kg/m)	2.3
Typical yield strength (kN)	490
Typical Ultimate tensile strength (kN)	530
Elongation %	5 - 7

Cable length (m)	Colour code	Cable length (m)	Colour code
4.0		10.0	
6.0		11.0	
8.0		12.0	
9.0			

To suit drill bit 52 – 55 mm

Cable Bolts








15.2mm Triple Strand Tendons & Trusses



Features:

- Low cost to capacity cable bolt configurations for the coal mining industry
- Can be used in either top-down or bottom-up grouting applications
- Typically fitted with fish-hooks to hold the cables inside the drill holes
- Truss configurations are available for ease of manually bending and tensioning cross members
- Birdcage spacing at 180mm for maximum bond strength with the grout and rock

Property	Typical Value
Strand diameter (mm)	15.2
Wire type	smooth
Bulb diameter (mm)	25
Bulb spacing (mm)	300
Steel area (mm ²)	420
Mass (kg/m)	3.4
Typical yield strength (kN)	735
Typical Ultimate tensile strength (kN)	795
Elongation %	5 - 7

Cable length (m)	Colour code	Cable length (m)	Colour code
4.0		10.0	
6.0		11.0	
8.0		12.0	
9.0			

To suit drill bit 52 – 55 mm

Cable Bolts








18mm Twin Strand Tendons & Trusses



Features:

- Low cost to capacity cable bolt configurations for the coal mining industry
- Can be used in either top-down or bottom-up grouting applications
- Typically fitted with fish-hooks to hold the cables inside the drill holes
- Truss configurations are available for ease of manually bending and tensioning cross members
- Birdcage spacing at 180mm for maximum bond strength with the grout and rock

Property	Typical Value
Strand diameter (mm)	18
Wire type	smooth
Bulb diameter (mm)	25
Bulb spacing (mm)	230
Steel area (mm ²)	380
Mass (kg/m)	3
Typical yield strength (kN)	600
Typical Ultimate tensile strength (kN)	706
Elongation %	5 - 7

Cable length (m)	Colour code	Cable length (m)	Colour code
4.0		10.0	
6.0		11.0	
8.0		12.0	
9.0			

To suit drill bit 52 – 55 mm

Cable Bolts








18mm Triple Strand Tendons & Trusses



Features:

- Low cost to capacity cable bolt configurations for the coal mining industry
- Can be used in either top-down or bottom-up grouting applications
- Typically fitted with fish-hooks to hold the cables inside the drill holes
- Truss configurations are available for ease of manually bending and tensioning cross members
- Birdcage spacing at 180mm for maximum bond strength with the grout and rock

Property	Typical Value
Strand diameter (mm)	18
Wire type	smooth
Bulb diameter (mm)	25
Bulb spacing (mm)	300
Steel area (mm ²)	570
Mass (kg/m)	4.5
Typical yield strength (kN)	900
Typical Ultimate tensile strength (kN)	1059
Elongation %	5 - 7

Cable length (m)	Colour code	Cable length (m)	Colour code
4.0		10.0	
6.0		11.0	
8.0		12.0	
9.0			

To suit drill bit 52 – 55 mm

Cable Bolt Accessories

31mm Barrel & Wedge



Features:

- Domed barrels & wedges are used with volcano plates to achieve installation angles of up to 18 degrees
- All barrels & wedges have an oil film coating and are pre-packaged in strong 4 litre buckets for corrosion protection
- All barrels & wedges to be pretensioned to a minimum 8 tonnes to ensure the wedge teeth penetrate the strand to achieve maximum load capacity
- To suit 31mm 12 wire SUMO and 31mm 10 wire Hollow cable
- Bucket lid colour = white for 70mm barrel
- Bucket lid colour = black for 90mm barrel

Cable Diameter (mm)	Barrel Length (mm)	Barrel Diameter (mm)	Unit Weight (kg)	Qty/Bucket
31	74	70	1.53	5
31	74	90	2.16	5

Cable Bolt Accessories

28.6mm Barrel & Wedge



Features:

- Domed barrels & wedges are used with volcano plates to achieve installation angles of up to 18 degrees
- All barrels & wedges have an oil film coating and are pre-packaged in strong 4 litre buckets for corrosion protection
- All barrels & wedges to be pretensioned to a minimum 8 tonnes to ensure the wedge teeth penetrate the strand to achieve maximum load capacity
- Suit Goliath cable bolts

Cable Diameter (mm)	Barrel Length (mm)	Barrel Diameter (mm)	Qty/Bucket
28.6	73	75	5

21.8mm Barrel & Wedge



Features:

- Domed barrels & wedges are used with volcano plates to achieve installation angles of up to 18 degrees
- All barrels & wedges have an oil film coating and are pre-packaged in strong 4 litre buckets for corrosion protection
- All barrels & wedges to be pretensioned to a minimum 8 tonnes to ensure the wedge teeth penetrate the strand to achieve maximum load capacity
- Suit 21.8mm Superstrand Cables
- Bucket lid colour = yellow

Cable Diameter (mm)	Barrel Length (mm)	Barrel Diameter (mm)	Qty/Bucket
22	60	58	10

Cable Bolt Accessories

18mm Barrel & Wedge



Features:

- Flat barrels & wedges are used with flat plates
- All barrels & wedges have an oil film coating and are pre-packaged in strong 4 litre buckets for corrosion protection
- All barrels & wedges to be pretensioned to a minimum 8 tonnes to ensure the wedge teeth penetrate the strand to achieve maximum load capacity
- Suit 18mm Twin and Triple Strand Tendons and Trusses
- Bucket lid colour = white

Cable Diameter (mm)	Barrel Length (mm)	Barrel Diameter (mm)	Unit Weight (kg)	Qty/Bucket
18	57	50	0.72	10

15.2mm Barrel & Wedge



Features:

- Flat barrels & wedges are used with flat plates
- All barrels & wedges have an oil film coating and are pre-packaged in strong 4 litre buckets for corrosion protection
- All barrels & wedges to be pretensioned to a minimum 8 tonnes to ensure the wedge teeth penetrate the strand to achieve maximum load capacity
- Suit 15.2mm Twin and Triple Strand Tendons and Trusses
- Bucket lid colour = white

Cable Diameter (mm)	Barrel Length (mm)	Barrel Diameter (mm)	Unit Weight (kg)	Qty/Bucket
15.2	44	42	0.42	20

Cable Bolt Accessories

Trussing Splice Tube



Features:

- Designed for joining truss tails
- All barrels & wedges to be pretensioned to a minimum 8 tonnes to ensure the wedge teeth penetrate the strand to achieve maximum load capacity
- Suit 15.2mm or 18mm Twin and Triple Strand Trusses

Length (mm)	Width (mm)	Unit Weight (kg)	Qty/Bucket
200	95	3.8	5

Grout Guns



Features:

- Pressure rated quick connection to poly grouting hose
- Easy to use even with heavy rubber grouting gloves
- Colour coded to suit the grout hose colour code

Suit Tube Diameter (mm)	Colour code	Rated Working Pressure (Bar)	Length (mm)	Unit Mass (kg)
16	Red	34.5	340	1.4
20	Yellow	34.5	340	1.4

Cable Bolt Accessories

Grout Lance – Screw In



Features:

- Suits common industry post groutable cable bolts
- Pressure rated
- Available with swivel to assist with screw in connection
- Available in length ranging from 200mm to 2000mm
- Available with either Minsup or Surelock fittings

Length (mm)	Thread Connection	Rated Working Pressure (Bar)
200 - 2000	½" BSP	200

Push-Clamp on Grout Guns




Features:

- Light weight
- Fast push and clamp on grout lance
- Available to suit numerous different cable bolts and hollow dowels

Suit Cable	Colour Code	Rated Working Pressure (Bar)	Length (mm)
SUMOTEX	Red	34.5	500 - 1800
JW10TEX	Yellow	34.5	500 - 1800
JW10	N/A	34.5	500 - 1800

Cable Bolt Accessories

Grout and Breather Tube



Features:

- Pressure rated
- Available in rolls or cut to length

Tube O.D. (mm)	Tube I.D. (mm)	Pressure rating	Mass (kg/m)	Length per roll	Colour code
5	3	n/a	0.01	200	
16	12.5	PN16	0.07	300	
20	16	PN16	0.11	300	

Cable Bolt Accessories

30T Tensioners



Features:

- 30 tonne cable bolt tensioner
- MDG41 specification
- Light weight
- Low operating pressure (370 Bar)
- Double acting to release tensioner off the cable under hydraulic power
- Patented design has engineered out possible pressure intensification within the double acting cylinder by having equal advance and retract ram areas.
- Suits up to 29mm diameter cable
- Patented design used special high capacity wedge setting springs to minimize tensioning bleed-off while maintaining a short tail on the cable bolts

Typical Applications:

- 31mm Hollow cables, Goliath cables, Sumo Cables and SuperStrand
- Can be connected to continuous miners, air tracks or portable air/hydraulic power packs

Tensioning Capacity (kN)	Max. Operating Pressure (Bar)	Ram Area (cm2)	Stroke (mm)	Weight (kg)	Min. strand length required (mm)
294	370	79.9	87	14	100

Cable Bolt Accessories

Tiger Dollie




Features:

- Exclusively used for tensioning of the "TOTO" device
- Suitable for both TG "TOTO" and SuperStrand "TOTO"
- Locking square drive
- Hardened socket for long life
- Sealed components to prevent contaminants entering and interfering with spring function

Drive (mm)	Length (mm)	Maximum Diameter (mm)	Mass (kg)	Socket
25mm square	460	70	5.5	ToTo device

Dolly suit TEX cables



Features:

- Lightweight design
- Long spigot to suit standard rigs and those with lobster rollers
- 55mm A.F. Hex socket

Drive (mm)	Length (mm)	Cable drive (mm)
25 square	500	55 A.F.

Cable Bolt Accessories

Dolly to suit 21.8mm Superstrand



Features:

- Use for installation of 19 wire 21.8mm Superstrand Cables
- Additional 36 A.F. Hex allows dual purpose use on M24 rock bolts
- Internal flower drive with water flush cleaning feature
- 25mm locking square drive for use with common coal mining bolting rigs

Drive (mm)	Length (mm)	Cable drive	Socket (mm)
25 square	350	Superstrand	36 A.F.

PLATES



Plates

Kanga Plate



Features:

- High load bearing characteristics
- Light weight and rounded corners
- Lesser tendency to cut mesh upon loading
- Varying combination plate applications available


Square dimension (mm)	Thickness (mm)	Hole diameter (mm)	Minimum Collapse load (kN)	Minimum Pull Through Load (kN)	Mass (kg)	Standard pack
150 x 150	5	38	201	201	0.85	980/pallet
150 x 150	6	38	245	245	1.02	980/pallet
200 x 200	5	38	201	201	1.53	500/pallet
200 x 200	6	38	245	245	1.83	500/pallet

Available with hanger slots

Available plain or hot dipped galvanised

Plates

Roof Bolt Volcano Plate



Features:


- Dome profile allows for 18° angles of alignment when installing the rock bolt with a domed ball washer
- Available as "rumbled" to take off sharp edges

Square dimension (mm)	Thickness (mm)	Hole diameter (mm)	Minimum Collapse load (kN)	Minimum Pull Through load (kN)	Mass (kg)	Standard pack
150 x 150	10	36	216	294	1.76	980/pallet

Available plain or hot dipped galvanised

Plates

Groutable Cable Volcano Plate - TEX, 70T SUMO & Hollow Cables



Features:


- Dome profile allows for 18° angles of alignment when installing the cable bolt with a domed barrel
- Grout indicator slots

Dimension (mm)	Thickness (mm)	Hole diameter (mm)	Minimum Collapse Load (kN)	Minimum Pull through load (kN)	Mass (kg)	Standard pack
300 x 300	12	56	294	441	8.5	100
300 x 300	12	69	343	392	8.5	100

Tested over a 150mm span

Plates

Cable Volcano Plate - Goliath



Features:


- Dome profile allows for 18° angles of alignment when installing the cable bolt with a domed barrel

Dimension (mm)	Thickness (mm)	Hole diameter (mm)	Minimum Collapse load (kN)	Minimum Pull through load (kN)	Mass (kg)	Standard pack
300 x 300	14	54	491	785	9.7	100

Tested over a 150mm span

Plates

Cable Volcano Plate - Superstrand



Features:


- Dome profile allows for 18° angles of alignment when installing the cable bolt with a domed barrel

Dimension (mm)	Thickness (mm)	Hole diameter (mm)	Minimum Collapse Load (kN)	Minimum Pull through load (kN)	Mass (kg)	Standard pack
200 x 200	12	42	147	343	3.8	200
200 x 200	14	40	196	441	4.3	200
300 x 300	12	42	147	343	8.5	100

Tested over a 150mm span

Plates

Flat Plate



Features:

- Can be supplied “rumbled” to take off edges. Unless specified, plates are supplied un-rumbled
- Used predominately with 15.2mm cable bolts. Can be supplied with 2 holes for cable bolting and grout tube application
- 200 x 200mm plates are often used on single tail twin-strand cable bolts with a flat barrel and wedge, Can be used in conjunction with a pizza pan
- Available as galvanised or black

Dimension (mm)	Thickness (mm)	Hole diameter (mm)	Mass (kg)	Standard pack
200 x 200	10	20	3.1	250

Plates

Domed Butterfly Plate



Features:

- A high tensile 2.4mm thick domed profile to provide the strength in a single bearing plate for rib support applications
- Has service slots for suspension of light items
- Has user friendly rounded corners
- Available as galvanised

Length (mm)	Width (mm)	Thickness (mm)	Hole diameter (mm)	Minimum Collapse load (kN)	Minimum Pull Through load (kN)	Mass (kg)	Standard pack
300	280	2.4	34	27	78	1.75	960/pallet

Plates

Surface Support Plates




Features:

- Rolled safety edges and corners to eliminate handling cuts
- Re-inforced rolls around the perimeter for extra rigidity
- Used in combination with a bearing plate, ideal for rib confinement
- Ideal for use on Husker Mesh on longwall bolt-ups


Length (mm)	Width (mm)	Thickness (mm)	Hole diameter (mm)	Mass (kg)	Standard pack
300	280	1.9	50	1.32	960/pallet
300	300	0.8	50	0.84	1000/pallet
450	450	0.8	50	1.59	250/pallet

MESH



Mesh

Steel Roof Mesh Module



Features:

- Turned edges for interlocking of modules and to maintain stiffness for ease of handling over the top of a continuous miner
- Re-inforced areas for lateral linking of roof bolts across the strata
- Wire diameters, spacing and overall dimensions can be customised to suit particular applications
- Customised paint lines along the modules to suit roof bolt patterns

Standard Roof Mesh Module

Wire diameter (mm)	Wire Typical UTS (kN)	Weld Strength* (kN)
5	8.5	7.5
5.6	12	
7	18	

*based on smallest wire diameter in welded joint

Available with combined galvanised and epoxy coating. Epoxy auto-ignition temperature 450 - 600 degrees C. Epoxy film thickness >300 microns.


Lightweight Sentinel Roof Mesh Module

Wire diameter (mm)	Wire Typical UTS (kN)	Weld Strength* (kN)
4	8.5	7.5
5	12	
5.6	18	

*based on smallest wire diameter in welded joint

Mesh

Steel Rib Mesh Sheet



Features:


- Typically flat sheets of smaller wire diameter and dimensions suitable for rib support
- Wire diameters, spacing and overall dimensions can be customized to suit particular applications

Wire diameter (mm)	Wire Typical UTS (kN)	Weld Strength (kN)
4	6.3	4.7
5	8.5	7.5

Available galvanised

Mesh

Plastic Mesh



Features:

- Available in rolls or custom cut flat sheets
- Commonly used for surface support that will later be cut by the continuous miner or longwall shearer


Minimum Tensile Strength (kN/m)	Minimum Elongation at Yield %	Aperture (mm)	Roll Dimensions (m)
22	10	61 x 61	28 x 2
45	10	65 x 65	50 x 2

Fire resistant to MDG3608

Available in flat sheets cut to custom dimensions

Mesh

Fibreglass Mesh




Features:

- Available in custom rigid flat sheets
- Commonly used for surface support that will later be cut by the continuous miner or longwall shearer

Rod Diameter (mm)	Breaking load of rod (kN)	Load at knot (kN)	Aperture (mm)
4	12.5	2-3	100 x 100
6	28	3-5	100 x 100

Available in flat sheets to custom dimensions

SPECIALTY GROUT & CEMENT



Specialty Grout and Cement

Bottom-Up 100 MPa Grout

Bottom-Up-100 is a pumpable cementitious grout for use as a bonding agent between a reinforcing member and the borehole wall in ground support systems. The product is packaged in durable water proof 20 kg bags for use in remote and harsh underground mining environments. The product is designed to minimise the risk of hard lumps entering pumping injection systems, which in turn minimises hazardous pressurisation and blockages.

Features:

- High strength 100 MPa cable bolt grout for "bottom-up" grouting
- Ready to use, mix with water and pump
- Excellent pumpability
- Non shrink, unique expansion system compensates for shrinkage
- Typically used with Bowen cables, 15.2mm triple/twin-strand cable bolts and trusses

Packaging:

- Durable water proof 20kg bags for use in remote and harsh underground mining environments
- 56 bags per pallet, 1.2 tonne per pallet



Uniaxial Compressive Strength* (MPa)			
	1 DAY	7 DAYS	28 DAYS**
5 litres/bag	60	100	105
6 litres/bag	55	90	100

*UCS independent test results were obtained using 50 x 50mm cubes

**28 day strength may vary between 85 MPa and 105 MPa depending on water content and testing methods utilised

Estimated yield 12 – 13 litres of grout at 5 – 6 litres of water per bag

Water : Grout Mix	5 - 6 litres per bag
Estimated Yield	12 - 13 litres per bag

Specialty Grouts and Cements

Top-Down 80 MPa Grout


Top-Down-80 is a pumpable cementitious grout for use as a bonding agent between a reinforcing member and the borehole wall in ground support systems. The product is packaged in durable water proof 20 kg bags for use in remote and harsh underground mining environments. The product is designed to minimise the risk of hard lumps entering pumping injection systems, which in turn minimises hazardous pressurisation and blockages.

Features:

- High strength 80 MPa thixotropic cable bolt grout for "top-down" grouting
- Ready to use, mix with water and pump
- Non shrink, unique expansion system compensates for shrinkage
- Excellent pumpability
- Typically used with TGBolt, Bulbed Superstrand and other "top-down" groutable cable bolts

Packaging:

- Durable water proof 20kg bags for use in remote and harsh underground mining environments
- 56 bags per pallet, 1.2 tonne per pallet



Uniaxial Compressive Strength* (MPa)			
	1 DAY	7 DAYS	28 DAYS**
6 litres/bag	43	77	89
7 litres/bag	33	63	80

*UCS independent test results were obtained using 50 x 50mm cubes

**28 day strength may vary between 70 MPa and 90 MPa depending on water content and testing method utilised

Estimated yield 13 – 14 litres of grout at 6 – 7 litres of water per bag

Water : Grout Mix	6 - 7 litres per bag
Estimated Yield	13 - 14 litres per bag

Specialty Grouts and Cements

Top-Down 80 Plus Grout

Top-Down-80PLUS is a pumpable cementitious grout for use as a bonding agent between a reinforcing member and the borehole wall in ground support systems. The product is specifically suited for long distance pumping up to 100 metres. TD80PLUS grout is packaged in durable water proof 20 kg bags for use in remote and harsh underground mining environments. The product is designed to minimise the risk of hard lumps entering pumping injection systems, which in turn minimises hazardous pressurisation and blockages.

Features:


- Highly thixotropic to enable top-down grouting
- High strength – 80 Mpa
- Excellent pumpability. Longer pumping distances achieved, up to 100 metres
- Shrinkage compensation maintains full grout contact between the ground support and borehole wall

Application:

- A high shear mechanical mixer is required
- Typical pump pressure requirement 500psi
- Maximum pumping distance 100m through a 25mm hose

Packaging:

- Durable water proof 20kg bags for use in remote and harsh underground mining environments
- 56 bags per pallet, 1.2 tonne per pallet



Uniaxial Compressive Strength* (MPa)			
	1 DAY	7 DAYS	28 DAYS**
6 litres/bag	43	77	89
7 litres/bag	33	63	80

*UCS independent test results were obtained using 50 x 50mm cubes

** 28 day strength may vary between 70 MPa and 90 MPa depending on water content and testing method utilised

Water : Grout Mix	6 - 7 litres per bag
Estimated Yield	13 - 14 litres per bag
Fresh Wet Density	2000 kg/m ³
Set Time	7 hrs
Expansion	1-3%

Specialty Grouts and Cements

J-PLUG GROUT

Jennchem's J-PLUG Grout is a pumpable cementitious grout designed for use in void filling applications and plugging of gas drainage holes.

Features:

- High volume output
- Non-shrink.
- Thixotropic
- Rapid setting

Application:

- Use a high shear mixer and potable water
- Water addition - 8.5L per 15Kg bag
- Once mixed the product is rapid setting
- Wash all equipment and pumping lines immediately after use

Technical Data – J-PLUG GROUT

Water:powder	Pump Life	Initial set time	Wet Density
0.56 :1	15-20 mins	30-40 mins	1850 Kg/m3

Uniaxial Compressive Strength (MPa)


1 day	7 days	28 days
3.5	10	20

Yield:

- One 15 Kg bag will typically yield 12.5 litres of grout

Packaging:

- 15Kg bags - 72 bags per pallet



Specialty Grouts and Cements

J-URR GROUT (Jennchem Underground Roadway Repair)

Jennchem J-URR GROUT is a specially formulated fast-setting concrete designed for the mining and tunnelling industries. J-URR GROUT is designed specifically for demanding applications where quick return to service is required, or where traditional concrete mixing equipment is unavailable or impractical. J-URR GROUT is formulated to absorb water and gain strength rapidly with no mixing. J-URRGROUT is ideal for rehabilitating underground roadways and filling mud holes and swillies. J-URR GROUT is a safer, more permanent solution than temporary bridges or traditional fill methods.

Features:

- Extremely Fast Setting
- Simple Application
- Quick return to service
- Safe to use
- Minimal dust make
- No mixing required
- Packaged in 1 tonne or 20kg bags
- Increases underground development production in wet conditions
- Fit for purpose QDS applicator available

Packaging:

- 20kg bags. (56 per pallet)
- 1 tonne bulk bags

Set / Cure Time

Foot Traffic	Light Duty Traffic (Driftrunner)	Heavy Duty Traffic (Shuttle car, Jumbo)	Extreme Duty Traffic (Continuous miner)
10 minutes	30 minutes	4 hours	8 hours

Note: Hot materials (and/or water) will accelerate set times and strength gain. Cold materials will slow set times and strength gain. pH and chemistry of water may affect set time and strength gain.



Shelf Life:

- One year when stored in cool dry conditions

Yield:

- 20kg: Approx. 15.4 litres
- 1000kg: Approx. 0.77m³

Application


- Repaired area is only as durable as the underlying substrate.
- Remove mud or soft base if possible, put down rock or ballast and compact to provide solid base.
- Fill hole or depression with water (if not already filled) up to where the repair level is desired.
- Open packaging and dump material into standing water.
- Allow material to soak up water.
- Agitation with a shovel or other suitable tool can be used to improve mixing.
- Finish to desired texture. This can be done in multiple lifts if required.

RESIN CAPSULES



Resin Capsules

SPIN2STALL® Resin Capsules



Features:

- Increased productivity – no waiting around for resin to cure before tightening the nut
- No counting of spin or hold times – consistent installations
- Self-auditing bolt installation – based upon remnant thread length of the bolt which provides an indication of the standard of installation
- High pre-tension levels can still be achieved
- Extensive research and independent testing shows minimal damage to resin bond using spin to stall technique
- Uses a J-Lok dual speed cure accelerated specifically formulated resin capsule and Jennmar bolt with engineered accurate and reliable pin break out level
- Available in fast set speeds usually incorporating 50:50 proportions of Fast A speed: slow set

Punched shear strength (MPa)	>22 MPa	
Shelf life (months)	4	
Capsule length (mm)	800 – 1000	1100 – 1400
Quantity / box	25	20
Quantity / pallet	1050	840

Grit limestone filler configuration

Must only be installed using spin2stall technique when used with the appropriate JX bolt and shear-pin.


*Relevant specifications are taken at 25°C

SPIN2STALL® is a registered trade mark of FCI Holdings Delaware, Inc

To mix, apply rotation and feed bolt up through the capsule at a rate of 1 sec per 100m of capsule (eg 1200mm capsule = 12 sec). Continue mixing at the back of the hole until the bolt is tightened to motor stall

Resin Capsules

Standard Dual Speed (Oil Based Catalyst) Resin Capsules



Features:

- Separate resin mastic and catalyst encased within a thin plastic film, sealed at each end by wire clips
- Standard oil based catalyst as approximately 7% of capsule volume
- For full encapsulation of pre-tensioned rock bolts
- Available in diameters of 25, (nominal), 26, 30, 36mm
- Available in dual speed ratios 50:50, 40:60
- Other combinations available on request

Punched shear strength (MPa)	>22 MPa		
Shelf life (months)	4		
Capsule length (mm)	800 – 1000	1100 – 1500	1600 – 1700
Quantity / box	25	20	15
Quantity / pallet	1050	840	720

Speed	Superfast/ slow	Extrafast/ slow	Fast/slow	Medium/ slow
Hold time (s)	10 - 60	12 - 60	14 - 60	19 - 60

Refer to individual box label for spin and hold installation instructions


Available in standard, grit and LIF limestone filler configurations

Capsules ≥ 1000 mm in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule (eg 1200mm capsule = 12 sec). Continue mixing at the back of the hole for an additional 2-4 seconds then wait for the resin to set.

Capsules < 1000 mm in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule. Continue mixing until the total mix time = 10 sec then wait for the resin to set.

Resin Capsules

Standard Single Speed (Oil Based Catalyst) Resin Capsules



Features:

- Separate resin mastic and catalyst encased within a thin plastic film, sealed at each end by wire clips
- Standard oil based catalyst as approximately 7% of capsules
- For general purpose anchoring of typical rebar rock bolts
- Available in diameters of 25, (nominal), 26, 30, 36mm
- Available gel times range from 10 seconds to 1.5 minutes

Punched shear strength (MPa)	>22 MPa		
Shelf life (months)	4		
Capsule length (mm)	800 – 1000	1100 – 1500	1600 – 1700
Quantity / box	25	20	15
Quantity / pallet	1050	840	720

Speed	Superfast	Extrafast	Fast	Medium	Slow
Hold time (s)	4	4	4	8	80

Refer to individual box label for spin and hold installation instructions


Available in standard, grit and LIF limestone filler configurations

Capsules ≥ 1000 mm in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule (eg 1200mm capsule = 12 sec). Continue mixing at the back of the hole for an additional 2-4 seconds then wait for the resin to set.

Capsules < 1000 mm in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule. Continue mixing until the total mix time = 10 sec then wait for the resin to set.

Resin Capsules

'5 Star' Dual Speed (Water Based Catalyst) Resin Capsules



Features:

- Water based catalyst as 20 – 30% of capsule volume compared to the traditional 5-10%
- Provides superior mixing
- Available in diameters of 25, (nominal), 26, 30, 36mm
- For full encapsulation of pre-tensioned rock bolts
- Cost effective

Punched shear strength (MPa)	>22 MPa		
Shelf life (months)	4		
Capsule length (mm)	800 – 1000	1100 – 1500	1600 – 1700
Quantity / box	25	20	15
Quantity / pallet	1050	840	720

Speed	Superfast/ Slow	Extrafast/ Slow	Fast/ Slow	Medium/ Slow
Hold time (s)	10 - 60	12 - 60	14 - 60	19 - 60

Refer to individual box label for spin and hold installation instructions


Available in standard or grit limestone filler configurations

Capsules ≥ 1000 mm in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule (eg 1200mm capsule = 12 sec). Continue mixing at the back of the hole for an additional 2-4 seconds then wait for the resin to set.

Capsules < 1000 mm in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule. Continue mixing until the total mix time = 10 sec then wait for the resin to set.

Resin Capsules

'5 Star' Single Speed (Water Based Catalyst) Resin Capsules



Features:

- Water based catalyst as 20 – 30% of capsule volume compared to the traditional 5-10%
- Provides superior mixing
- Available in diameters of 25, (nominal), 26, 30, 36mm
- For anchoring of all types of rock bolts
- Cost effective

Punched shear strength (MPa)	>22 MPa		
Shelf life (months)	4		
Capsule length (mm)	800 – 1000	1100 – 1500	1600 – 1700
Quantity / box	25	20	15
Quantity / pallet	1050	840	720

Speed	Superfast	Extrafast	Fast	Medium	Slow
Hold time (s)	4	4	4	8	80

Refer to individual box label for spin and hold installation instructions


Available in standard or grit limestone filler configurations

Capsules ≥ 1000 mm in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule (eg 1200mm capsule = 12 sec). Continue mixing at the back of the hole for an additional 2-4 seconds then wait for the resin to set.

Capsules < 1000 mm in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule. Continue mixing until the total mix time = 10 sec then wait for the resin to set.

Resin Capsules

Post Grout Cable (Water Based Catalyst) Resin Capsules



Features:

- Designed for Point Anchoring of cable bolts for tensioning prior to being post grouted
- Catalyst compartment comprising 20 % of the capsule volume
- Improved mixing of resins in larger diameter drill holes
- Cost effective
- Comes with resin retainer

Punched shear strength (MPa)	>22 MPa		
Shelf life (months)	4		
Capsule length (mm)	650	800 – 1000	1200
Quantity / box	15	10	9
Quantity / pallet	720	420	378

Speed	Medium	Slow
Hold time (s)	19	80

Refer to individual box label for spin and hold installation instructions


Available in standard or grit limestone filler configurations

Capsules $\geq 1000\text{mm}$ in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule (eg 1200mm capsule = 12 sec). Continue mixing at the back of the hole for an additional 2-4 seconds then wait for the resin to set.

Capsules $< 1000\text{mm}$ in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule. Continue mixing until the total mix time = 10 sec then wait for the resin to set.

Resin Capsules

Post Grout Cable (Oil Based Catalyst) Resin Capsules



Features:

- Designed for Point Anchoring of cable bolts for tensioning prior to being post grouted
- Catalyst compartment comprising 7% of the capsule volume
- Comes with resin retainer

Punched shear strength (MPa)	>22 MPa		
Shelf life (months)	4		
Capsule length (mm)	650	800 – 1000	1200
Quantity / box	15	10	9
Quantity / pallet	720	420	378

Speed	Medium	Slow
Hold time (s)	19	80


Refer to individual box label for spin and hold installation instructions

Capsules ≥ 1000 mm in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule (eg 1200mm capsule = 12 sec). Continue mixing at the back of the hole for an additional 2-4 seconds then wait for the resin to set.

Capsules < 1000 mm in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule. Continue mixing until the total mix time = 10 sec then wait for the resin to set.

Resin Capsules

Twin 'H' Resins (Oil Based Catalyst) Resin Capsules



Features:

- Low insertion force formulation
- For anchoring flexible cable tendons in a small annulus
- Separate resin mastic and catalyst encased within a thin plastic film, sealed at each end by wire clips
- Oil based catalyst as 7% of capsule
- Typical nominal diameter of 25mm
- Available gel times of 90 seconds and 20 minutes

Punched shear strength (MPa)	>22 MPa	
Shelf life (months)	4	
Capsule length (mm)	1650	2200
Capsule diameter (mm)	32	25.5
Quantity / box	8	11

Speed	Fast/XXSlow	Medium/XXSlow
Hold time (s)	12 - 1200	19-1200

Refer to individual box label for spin and hold installation instructions

Available in standard, grit and LIF limestone filler configurations

Capsules $\geq 1000\text{mm}$ in length: To mix, apply rotation and feed the bolt up through the capsule at a rate of 1 sec per 100mm of capsule (eg 1200mm capsule = 12 sec). Continue mixing at the back of the hole for an additional 2-4 seconds then wait for the resin to set.

CUTTABLE SUPPORT & CUTTABLE SUPPORT ACCESSORIES



Cuttable Support

32mm Torque Tension Bolt



Features:

- High capacity support for coal rib support where extraction includes cutting of bolts
- 46mm Hex nut
- Break-out cap is designed to break into small pieces to clear easily from spanners/dollies
- "V" Notch end to promote shredding of the resin capsule film
- Continuous rope thread providing deformations for resin mixing and high bond strength with the rock
- J-Lok resin capsules available in 32 – 36mm diameter for maximum encapsulation
- Both 200mm and 300mm square plastic steel inserted plates with 51mm holes available to suit this product
- Do not store these products in direct sunlight

Property	Minimum Value
Ultimate Tensile Strength of Rod (kN)	500
Ultimate Tensile strength with Nut (kN)	90
Single Shear Strength (kN)	110
Rod Torsional Strength (Nm)	200
Elongation %	2
Cross sectional area (mm ²)	730
Thread pitch (mm)	10
Mass/meter (kg/m)	1.45

Break-out Nut	White
Torque Setting (N.m)	130 - 175
Rod Colour	

To suit drill bit 38 - 42mm

Cuttable Support

32mm GEODOWEL



Features:

- High capacity post groutable fibreglass dowel
- Used where coal extraction includes cutting of rib support dowels
- Suitable for use with common mine site cable bolting consumables:
 - 36mm diameter resin capsules
 - Cable bolt grouts
- 46mm Hex Nut
- Purpose designed installation spanners and grout connectors available
- Custom configurations are available including;
 - Resin anchored, tensioned, post grouted dowel
 - Simple fully grouted dowel
- Hollow dowels stocked in 3m and 4m lengths
- Do not store these products in direct sunlight

Property	Minimum Value
Ultimate Tensile Strength of Rod (kN)	500
Ultimate Tensile strength with Nut (kN)	160
Shear Strength (kN)	140
Rod Torsional Strength (Nm)	150
Elongation %	2
Cross sectional area (mm ²)	610
Thread pitch (mm)	10
Mass/meter (kg/m)	1.3

Rod Colour	White
------------	-------

To suit drill bit 42 - 45mm

Cuttable Support

22mm Thrust Dowel



Features:

- Used for coal rib support where extraction includes cutting of bolts
- Patented high strength over-moulded polymer head achieves double the strength of standard fiberglass nuts
- Coloured over-moulding polymer provides length colour code after installation
- Thrust dowels eliminate tails protruding
 - Reducing the risk of damage to rib support by mobile equipment
 - Reduces risk of personal injury when walking around equipment installations
- "V" Notch end to promote shredding of the resin capsule film
- Continuous rope thread providing large deformations for resin mixing and high bond strength with the rock
- 22mm diameter dowel for high strength and maximum encapsulation by volume
- Do not store these products in direct sunlight

Property	Minimum Value
Ultimate Tensile Strength of Rod (kN)	230
Molded Head Tensile Strength (kN)	120
Single Shear Strength (kN)	50
Rod Torsional Strength (Nm)	80
Elongation %	2
Cross sectional area (mm ²)	340
Thread pitch (mm)	10
Mass/meter (kg/m)	0.61

Bolt length (mm)	Head colour code
1150	Blue
1450	Yellow
1750	Red

Rod colour	Black
------------	-------

To suit drill bit 27 – 28mm

Cutable Support







25mm Thrust Dowel



Features:

- Used for coal rib support where extraction includes cutting of bolts
- Thrust dowels eliminate tails protruding
 - Reducing the risk of damage to rib support by mobile equipment
 - Reduces risk of personal injury when walking around equipment installations
- "V" Notch end to promote shredding of the resin capsule film
- Continuous rope thread providing large deformations for resin mixing and high bond strength with the rock
- 25mm diameter dowel for high strength and maximum encapsulation by volume
- Do not store these products in direct sunlight

Property	Minimum Value
Ultimate Tensile Strength of Rod (kN)	300
Ultimate Tensile strength with Nut (kN)	120
Single Shear Strength (kN)	70
Rod Torsional Strength (Nm)	110
Elongation %	2
Cross sectional area (mm ²)	434
Thread pitch (mm)	10
Mass/meter (kg/m)	0.95

Bolt length (m)	Rod & Head colour	
1150mm		
1450mm		
1750		

To suit drill bit 28mm

Cuttable Support

22mm Extra High Torsion (XHT) Tensionable Bolt



Features:

- Used for coal rib support where extraction includes cutting of bolts
- Extra high torsional strength material minimises risk of damage to fiberglass when tightening
- Break-out cap is designed to break into small pieces to clear easily from spanners/dollies
- "V" Notch end to promote shredding of the resin capsule film
- Continuous rope thread providing large deformations for resin mixing and high bond strength with the rock
- 22mm diameter dowel for high strength and maximum encapsulation by volume
- Recommended for drill hole diameters 27 - 28mm

Property	Minimum Value
Ultimate Tensile Strength of Rod (kN)	210
Ultimate Tensile strength with Nut (kN)	60
Single Shear Strength (kN)	50
Rod Torsional Strength (Nm)	250
Elongation %	2
Cross sectional area (mm ²)	340
Thread pitch (mm)	10
Mass/meter (kg/m)	0.61

Break-out Nut	Torque Setting (N.m)
White	80 - 110
	30 - 50

Rod colour	
------------	--

To suit drill bit 27 – 28mm

Cuttable Support

Plastic Plates: 22 - 25mm Dowels




Features:

- Used as coal rib surface support where extraction involved cutting the support
- Compatible with Jennmar 22mm dowels
- Flexibility of all plastic allow conforming to shape of uneven coal rib
- Tested to ensure no splitting under severe deformation found in uneven coal ribs
- Square plate is designed to visually turn corners upon applying hydraulic rib bolter thrust
- Do not store these in direct sunlight

Dimension (mm)	Hole diameter (mm)	Minimum Pull through load (kN)	Mass (kg)	Standard pack	Compatible Bolt dia (mm)
230 round	33	20	0.3	1000	22 and 25
230 square	33	12	0.3	1000	22 and 25

Cutable Support

Plastic Steel Combination Plates - 22-25mm Dowels



Features:


- Used as coal rib surface support where extraction involved cutting the support
- Thin 3mm steel plate encased within the main plate provides up to 3 times the strength of a standard plastic plate
- Superior strength is compatible with new improved fiberglass dowels
- Steel inserts allow use of bolting rig magnetic holders
- Steel plate thin gauge and rounded corners minimize risk of conveyor belt damage
- Do not store these products in direct sunlight

Dimension (mm)	Hole diameter (mm)	Minimum Pull through load (kN)	Mass (kg)	Standard pack	Compatible Bolt diameter (mm)
230 round	33	50	0.6	500	22
200 x 200 square	33	50	0.7	1000	22
200 x 200 square	42	50	0.7	1000	22 and 25
300 x 300 square	33	50	1	1000	22
300 x 300 square	42	50	1	1000	22 and 25

Tested over a 150mm span

Cutable Support

Plastic Steel Combination Plates - 32mm Dowels



Features:

- Used as coal rib surface support where extraction involved cutting the support
- Thin 3mm steel plate encased within the main plate provides up to 3 times the strength of a standard plastic plate
- Superior strength is compatible with new improved fiberglass dowels
- Steel inserts allow use of bolting rig magnetic holders
- Steel plate thin gauge and rounded corners minimize risk of conveyor belt damage
- Do not store these products in direct sunlight

Dimension (mm)	Hole diameter (mm)	Minimum Pull through load (kN)	Mass (kg)	Standard pack	Compatible Bolt diameter (mm)
200 x 200 square	51	90	0.7	1000	32
300 x 300 square	51	90	1	1000	32

Cuttable Support Accessories

46 A.F. Dolly



Features:

- 25mm locking square drive to suit standard coal mining bolting equipment
- Socket designed to promote clean cap break-out on JENNMAR 32mm dowel

Drive (mm)	Length (mm)	Socket (mm)
25 square	300 – 600	46 Hex

Grout Connector Suit 32mm Dowels



Features:

- Adapts to 32mm hollow fibreglass dowel for:
 - Installation mixing using a standard 36mm A.F. roof bolt dolly
 - Grouting connection by BSP thread within the Hex section
- Can be re-used

Hex (mm)	Length (mm)	Diameter (mm)	Rated Working Pressure (Bar)
36 A.F.	90	45	34.5

Can be used to spin the dowel through the resin, and also to pump grout after anchoring

WWW.JENNMAR.COM.AU

Head Office and Plant

40-44 Anzac Avenue, Smeaton Grange NSW 2567

Ph: +61 2 4648 7500

Fax: +61 2 4648 7555

Queensland Plant

48-50 Southgate Drive, Paget QLD 4740

Ph: +61 7 4952 8700

Fax: +61 7 4952 8777

Perth Plant

84 Furniss Road, Lansdale WA 6065

Ph: +61 8 9408 9900

Fax: +61 8 9408 9999



NOTE: Please confirm that you have the latest version of this catalogue by visiting www.jennmar.com.au before using any of the technical specifications contained herein.

JA032022F